
# Orchestrating Networked Entities

Charles Consel
The Phoenix Research Group




#### Phoenix research group

- 2 researchers
- 2 research engineers,
- 6 PhD students



### Phoenix research group Network-Centric Platforms






- Avionics
- Telecommunications and networking
- Pervasive computing:
  - Home/building automation

Cockpit

Altimeter

**Engines** 

Assisted living



Lights

gauge

Rudder

Tool-based approach to developing applications that orchestrate resources within a platform



#### Phoenix research group

#### Research theme:

A language-based approach to software development

#### We develop:


- Language constructs to describe software systems
- Compilation techniques to support and guide programming
- Verification techniques to ensure :
  - Functional properties (e.g., implementation conformance)
  - Non-functional properties (QoS and fault tolerance)

Web site: http://phoenix.inria.fr






Our Integrated Approach



supports the programmer all along the development cycle




### The Sense/Compute/Control (SCC) Paradigm






#### Example: Intrusion/Access Management





### Specification-Driven Approach






#### **Taxonomy Specification**

```
structure Location {
 name as String;
device LocatedDevice {
 attribute location as Location;
                                                           Alarm
device Alarm extends LocatedDevice {
                                                           OnOff
 action OnOff { on(); off(); }
device MotionDetector extends LocatedDevice {
                                                            detection
                                                            Motion
 source detection as Boolean;
                                                            Detector
```




#### **Application Specification**

```
context Presence as Boolean
    indexed by location as Location {
  source detection from MotionDetector;
context Intrusion as Boolean
    indexed by location as Location {
  context Presence;
  context SecureBuilding;
controller IntrusionManager {
  context Intrusion;
  context SceneImage;
  action OnOff on Alarm;
 action Display on SurveillanceScreen;
```





## Specification-Driven Approach






# Implementation using The Dedicated Programming Support

```
public class IntrusionManagerImpl extends IntrusionManager {
   @Override
   public void onNewIntrusion(Boolean intrusion,
                              Location location) {
      if (intrusion) {
         allAlarms().on();
         allSurveillanceScreens().alert(true);
         Image sceneImage = getSceneImage(location);
         if (sceneImage != null) {
             allSurveillanceScreens().
                 displayImage(sceneImage, location);
      } else {
         allAlarms().off();
         allSurveillanceScreens().alert(false);
```




# Specification-Driven Approach






#### Simulation Scenario Editor



#### Simulation Scenario Execution





### Ongoing and future research directions

- Architecturing error handling
- Architecturing security
- Architecturing QoS
- Certifying architectures (incrementally)
- Monitoring software systems
- Comparing software development approaches
- Hybrid systems

- Home/building automation
- Assisted living / Patient monitoring
- Avionics / Drones
- Secure open platforms

