

Simple maps: distances and convergence

Gwendal Collet (TU Wien)

joint work with Marie Albenque (LIX), Olivier Bernardi (Brandeis University) and Éric Fusy (LIX)


JCB 2015

February 3rd 2015

Random simple maps


Simple planar map: rooted planar map with no loops nor multiple edges = planar graph embedded on the sphere, considered up to continuous deformation.

$\mathcal{S}_n = \{ \text{Simple maps with } n \text{ edges} \}$
 $\mathcal{S}'_n = \text{uniform random element of } \mathcal{S}_n$



Random simple maps

Simple planar map: rooted planar map with no loops nor multiple edges = planar graph embedded on the sphere, considered up to continuous deformation.



$\mathcal{S}_n = \{ \text{Simple maps with } n \text{ edges} \}$
 $S_n = \text{uniform random element of } \mathcal{S}_n$

$(V(\mathcal{S}_n), d_{gr})$ metric space for graph distance

Behaviour of S_n when n goes to infinity?

Typical distance? Distance distribution? Scaling limit?

Remark: Study of outertriangular simple maps is enough
→ Simple map has a.s. a giant outertriangular core

Random simple maps

$(V(S_n), d_{gr})$ metric space for graph distance

Behaviour of S_n when n goes to infinity?

Typical distance? Distance distribution? Scaling limit?

Well known:

→ Chassaing–Schaeffer (2004):

typical distance in rooted plane quadrangulations

with n faces $\sim n^{1/4}$ when $n \rightarrow \infty$

+ distance profile converges towards **ISE**

→ Le Gall (2007, 2012), Miermont (2012):

quadrangulations converge towards the **Brownian map**

when rescaled by $n^{-1/4}$


extended to $2p$ -angulations and triangulations

→ Abraham (2013): Bipartite maps

→ Addario-Berry–Albenque (2013):

simple triangulations and simple quadrangulations

→ Bettinelli–Jacob–Miermont (2013): General maps



Random simple maps

$(V(S_n), d_{gr})$ metric space for graph distance

Behaviour of S_n when n goes to infinity?

Typical distance? Distance distribution? Scaling limit?

Well known:

→ Chassaing–Schaeffer (2004):

typical distance in rooted plane quadrangulations

with n faces $\sim n^{1/4}$ when $n \rightarrow \infty$

+ distance profile converges towards **ISE**

→ Le Gall (2007, 2012), Miermont (2012):

quadrangulations converge towards the **Brownian map**

when rescaled by $n^{-1/4}$

extended to $2p$ -angulations and triangulations

→ Abraham (2013): Bipartite maps

→ Addario-Berry–Albenque (2013):

simple triangulations and simple quadrangulations

→ Bettinelli–Jacob–Miermont (2013): General maps



Random simple maps

$(V(S_n), d_{gr})$ metric space for graph distance

Behaviour of S_n when n goes to infinity?

Typical distance? Distance distribution? Scaling limit?

Brownian map universal limit for "reasonable" classes of maps

Idea: General method in Le Gall (2013)

- Encode maps with some (labeled, blossoming...) trees
- Study the limit of these trees
- Interpret distance on the map as a function on the tree
- Technical conditions: tightness, invariance upon rerooting

The results

$\forall e \in E(S_n) : d_{S_n}(e) = \text{length of the shortest path from } e \text{ to } e_0$

Profile : $(f_k)_{k \geq 1}$, where $f_k := \frac{1}{n} \sum_{e \in E_M} \delta_{d_{S_n}(e)}$

Radius : $r(M) := \max(d(e), e \in E_M)$

Theorem [Bernardi, C., Fusy 2014]:

$f_k / (2n)^{1/4} \xrightarrow{(d)}$ ISE positively shifted

$r / (2n)^{1/4} \xrightarrow{(d)}$ width of ISE (also holds for moments)

Theorem [Albenque, Bernardi, C., Fusy 2015]:

$\left(V(S_n), \left(\frac{1}{2n} \right)^{1/4} d_{S_n} \right) \xrightarrow{(d)} (M, D^*)$ Brownian map
for the distance of Gromov–Hausdorff on metric spaces.

Remark: Same rescaling factor $n^{1/4}$, typical of planar maps

Orientation for outertriangular simple maps


3-orientation with buds=

orientation of edges and outgoing **buds** s.t.:

$$\text{out}(\bullet) = 1$$

$$\text{out}(\circ) = 3$$

+ each face of degree $d + 3$ has d buds



Orientation for outertriangular simple maps

3-orientation with buds=

orientation of edges and outgoing **buds** s.t.:

$$\text{out}(\bullet) = 1$$


$$\text{out}(\circ) = 3$$


+ each face of degree $d + 3$ has d buds

[Bernardi, Fusy '10]


These orientations characterize
outertriangular simple maps

Moreover, there is a **unique** one
without clockwise circuit and with

local rule: 



Rightmost paths (RMP) in simple maps



S_n endowed with its 3-orientation
 e_0 root, $e \in E(S_n)$:

$d_{RM}(e)$ = length of the rightmost
path from e to e_0

[Addario-Berry, Albenque '13] (adapted to simple maps)

For $\epsilon > 0$, let $A_{n,\epsilon}$ be the event that there exists $e \in S_n$ such that $d_{RM}(e) \geq d_{S_n}(e) + \epsilon n^{1/4}$




Then under the uniform law on S_n , for all $\epsilon > 0$: $\mathcal{P}(A_{n,\epsilon}) \rightarrow 0$

\Rightarrow Rightmost paths are almost surely quasi-geodesic

\Rightarrow We can consider profile of d_{RM} , up to $n^{1/4}$ scaling




Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Bijection with eulerian triangulations

First step: Inflate inner edges and vertices





Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Second step: Merge remaining edges

degree $2d + 3$





Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Second step: Merge remaining edges

degree $2d + 3$





Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Second step: Merge remaining edges

degree $2d + 3$





Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Second step: Merge remaining edges

degree $2d + 3$





Bijection with eulerian triangulations

First step: Inflate inner edges and vertices




Second step: Merge remaining edges

degree $2d + 3$




Eulerian triangulation

Distance profile



Outertriangular simple map



Eulerian triangulation


Remark: Preserves rightmost paths

$\Rightarrow d_{S_n} \approx d_{RM} \approx \text{distance in oriented forest}$


Distance profile

[Chassaing–Schaeffer 2004], [Le Gall 2006]:

The distance profile in the oriented forest of a rooted eulerian triangulation, rescaled by $(2n)^{-1/4}$, converges to positively shifted ISE.



Eulerian triangulation with $2n$ faces with vertices labelled by geodesic distance





very-well-labelled tree rooted on a vertex of minimum label

Distance profile

[Chassaing–Schaeffer 2004], [Le Gall 2006]:

The distance profile in the oriented forest of a rooted eulerian triangulation, rescaled by $(2n)^{-1/4}$, converges to positively shifted **ISE**.

labelled Galton-Walson tree
where the labels behave as a
random walk on the tree



very-well-labelled tree rooted
on a vertex of minimum label

Encoding with trees: first bijection

[Bousquet-Mélou–Schaeffer 2004] (specialization):

There is a bijection between:

Rooted eulerian triangulations
with $2n$ faces



Balanced oriented binary trees
with $n - 1$ inner edges

Encoding with trees: first bijection


[Bousquet-Mélou–Schaeffer 2004] (specialization):

There is a bijection between:

Rooted eulerian triangulations
with $2n$ faces



Balanced oriented binary trees
with $n - 1$ inner edges



- Rooted binary tree with oriented inner edges

Encoding with trees: first bijection


[Bousquet-Mélou–Schaeffer 2004] (specialization):

There is a bijection between:

Rooted eulerian triangulations
with $2n$ faces



Balanced oriented binary trees
with $n - 1$ inner edges



- Rooted binary tree with oriented inner edges
- Apply the following rule:



Encoding with trees: first bijection


[Bousquet-Mélou–Schaeffer 2004] (specialization):

There is a bijection between:


Rooted eulerian triangulations
with $2n$ faces



Balanced oriented binary trees
with $n - 1$ inner edges



- Rooted binary tree with oriented inner edges
- Apply the following rule:



- Closure à la Schaeffer
3 unmatched edges

root unmatched = balanced

Encoding with trees: first bijection


[Bousquet-Mélou–Schaeffer 2004] (specialization):

There is a bijection between:


Rooted eulerian triangulations
with $2n$ faces



Balanced oriented binary trees
with $n - 1$ inner edges



- Rooted binary tree with oriented inner edges
- Apply the following rule:



- Closure *à la* Schaeffer
3 unmatched edges

root unmatched = balanced

- Unmatched edges closed
at ∞ to obtain a rooted
bipartite cubic map

→ dual of eulerian triangulations

Encoding with trees: first bijection



There is a bijection between:

Rooted outertriangular simple maps
with $n + 2$ edges



Balanced oriented binary trees
with $n - 1$ inner edges

- Apply the following rule:



Encoding with trees: first bijection



There is a bijection between:

Rooted outertriangular simple maps
with $n + 2$ edges



Balanced oriented binary trees
with $n - 1$ inner edges

- Apply the following rule:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:



- Add 3 outer vertices and close remaining buds


Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:



- Add 3 outer vertices and close remaining buds


Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:



- Add 3 outer vertices and close remaining buds
- Connect outer vertices to form the outer triangle


Encoding with trees: first bijection

There is a bijection between:


Rooted outertriangular simple maps
with $n + 2$ edges




Balanced oriented binary trees
with $n - 1$ inner edges



- Apply the following rule:



- Counterclockwise closure:




- Add 3 outer vertices and close remaining buds
- Connect outer vertices to form the outer triangle

Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners


- $\text{label}(\text{root}) = 0$



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners


- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf $+1$



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf $+1$
ingoing edge -1




Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf $+1$
ingoing edge -1

\approx depth of the face in the bicubic map




Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf +1
ingoing edge -1

\approx depth of the face in the bicubic map


- Unmatched leaves =
last 0, 1 and 2 corners



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
 - Counterclockwise: leaf +1
ingoing edge -1
- \approx depth of the face in the bicubic map




- Unmatched leaves = last 0, 1 and 2 corners
- Apply the following rule:



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
 - Counterclockwise: leaf +1
ingoing edge -1
- \approx depth of the face in the bicubic map




- Unmatched leaves = last 0, 1 and 2 corners

- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf +1
ingoing edge -1


\approx depth of the face in the bicubic map



- Unmatched leaves = last 0, 1 and 2 corners
- Apply the following rule:



- Counterclockwise closure:




Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf +1
ingoing edge -1


\approx depth of the face in the bicubic map



- Unmatched leaves = last 0, 1 and 2 corners
- Apply the following rule:




- Counterclockwise closure:



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners


- $\text{label}(\text{root}) = 0$
 - Counterclockwise: leaf +1
ingoing edge -1
- \approx depth of the face in the bicubic map



- Unmatched leaves = last 0, 1 and 2 corners
- Apply the following rule:




- Counterclockwise closure:



Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
 - Counterclockwise: leaf +1
ingoing edge -1
- \approx depth of the face in the bicubic map




- Unmatched leaves = last 0, 1 and 2 corners

- Apply the following rule:



- Counterclockwise closure:




- Add 3 outer vertices and close remaining buds

Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
 - Counterclockwise: leaf +1
ingoing edge -1
- \approx depth of the face in the bicubic map




- Unmatched leaves = last 0, 1 and 2 corners

- Apply the following rule:



- Counterclockwise closure:




- Add 3 outer vertices and close remaining buds

Encoding with trees: second bijection

Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf +1
ingoing edge -1

\approx depth of the face in the bicubic map




- Unmatched leaves = last 0, 1 and 2 corners

- Apply the following rule:



- Counterclockwise closure:




- Add 3 outer vertices and close remaining buds

Encoding with trees: second bijection





Idea: Shortcut the bicubic maps with labels on corners

- $\text{label}(\text{root}) = 0$
- Counterclockwise: leaf $+1$
ingoing edge -1
 \approx depth of the face in the bicubic map




Outertriangular simple map
label = length of RMP

From oriented binary trees to labeled trees



From oriented binary trees to labeled trees




Labeled trees = Galton-Watson trees with random displacements on edges

[Marckert '08] Converges to Brownian snake when labels rescaled by $(2n)^{1/4}$

Study of the limit of labeled trees

Contour and label processes of a labeled tree





[Marckert '08]

For a sequence in \mathcal{S}_n , and the associated labeled trees $(T_n)_{n \geq 0}$:

$$\left((8n)^{-1/2} C_n(\lfloor nt \rfloor), (2n)^{-1/4} \tilde{Z}_n(\lfloor nt \rfloor) \right)_{0 \leq t \leq 1} \xrightarrow[n \rightarrow \infty]{(d)} (e_t, Z_t)_{0 \leq t \leq 1}$$


Brownian snake




[Aldous] Brownian tree

+ Brownian motion conditioned on the tree

Interpretation of the distances




Interpretation of the distances




Interpretation of the distances

$$\check{Z}_{u,v} = \min\{Z_s, u \leq s \leq v\}$$




Interpretation of the distances



Interpretation of the distances

$$\check{Z}_{u,v} = \min\{\check{Z}_s, u \leq s \leq v\}$$




Blue path of length: $\check{Z}_u + \check{Z}_v - 2\check{Z}_{u,v} + 2$

Since $(n^{-1/4}\check{Z}_n)$ converges, $(d_n)_{n \geq 0}$ tight

Interpretation of the distances

$$\check{Z}_{u,v} = \min\{\check{Z}_s, u \leq s \leq v\}$$




Blue path of length: $\check{Z}_u + \check{Z}_v - 2\check{Z}_{u,v} + 2$

Since $(n^{-1/4}\check{Z}_n)$ converges, $(d_n)_{n \geq 0}$ tight

$$d_{S_n} \leq \check{Z}_u + \check{Z}_v - 2\check{Z}_{u,v} + 2 \xrightarrow{(d)} D^* \text{ distance in the Brownian map}$$

Interpretation of the distances



$d_{S_n} \leq \check{Z}_u + \check{Z}_v - 2\check{Z}_{u,v} + 2 \xrightarrow{(d)} D^*$ distance in the Brownian map

$$D^\circ(s, t) = Z_s + Z_t - 2 \max\left\{ \inf_{s \leq u \leq t} Z_u, \inf_{t \leq u \leq s} Z_v \right\}$$

$$D^*(a, b) = \inf \left\{ \sum_{i=0}^{k-1} D^\circ(a_i, a_{i+1}) : k \geq 1, a = a_1, \dots, a_k = b \right\}$$

Thank you!

