

Reachability for Two-Counter Machines with One Test and One Reset

Alain Finkel¹ Jérôme Leroux² Grégoire Sutre²


¹LSV, ENS Paris-Saclay, CNRS, Université Paris-Saclay, France

²LaBRI, Univ. Bordeaux, CNRS, Bordeaux-INP, Talence, France


LaBRI/MF Seminar, March 2019

Paper available online in the proceedings of FSTTCS 2018

A Two-Counter Machine with One Test and One Reset




A Two-Counter Machine with One Test and One Reset




$p(1, 0) \rightarrow q(2, 0) \rightarrow q(0, 4) \not\rightarrow q$

A Two-Counter Machine with One Test and One Reset



$p(1, 0) \rightarrow q(2, 0) \rightarrow q(0, 4) \not\rightarrow q$
 $\rightarrow r(0, 4) \rightarrow r(2, 2) \rightarrow p(2, 0)$

A Two-Counter Machine with One Test and One Reset



$p(1, 0) \rightarrow q(2, 0) \rightarrow q(0, 4) \not\rightarrow q$
 $\rightarrow r(0, 4) \rightarrow r(2, 2) \rightarrow p(2, 0)$

$p(2, 0) \rightarrow q(3, 0) \rightarrow q(1, 4) \not\rightarrow q$
 $\not\rightarrow r$

VASS Extended with Tests, Resets and Transfers

Definition

A d -dim VASS is a triple $\langle Q, \Sigma, \Delta \rangle$ where

- Q : finite set of **states**
- Σ : finite set of **actions**, with

$$\Sigma \subseteq \mathbb{Z}^d$$

- $\Delta \subseteq Q \times \Sigma \times Q$: finite set of **transitions**

Configurations: $q(\mathbf{x})$ with $q \in Q$ and $\mathbf{x} \in \mathbb{N}^d$

$$(a_1, a_2) \in \mathbb{Z}^2 \quad \text{stands for} \quad (c_1, c_2) \leftarrow (c_1 + a_1, c_2 + a_2)$$

VASS Extended with Tests, Resets and Transfers

Definition

A d -dim **Extended VASS** is a triple $\langle Q, \Sigma, \Delta \rangle$ where

- Q : finite set of **states**
- Σ : finite set of **actions**, with

$$\Sigma \subseteq \mathbb{Z}^d \cup \{T(i), R(i), Tr(i,j) \mid i, j \in \{1, \dots, d\}, i \neq j\}$$

- $\Delta \subseteq Q \times \Sigma \times Q$: finite set of **transitions**

Configurations: $q(\mathbf{x})$ with $q \in Q$ and $\mathbf{x} \in \mathbb{N}^d$

$(a_1, a_2) \in \mathbb{Z}^2$	stands for	$(c_1, c_2) \leftarrow (c_1 + a_1, c_2 + a_2)$
$T(1)$		$c_1 == 0$
$R(2)$		$c_2 \leftarrow 0$
$Tr(1, 2)$		$c_2 \leftarrow c_2 + c_1 ; c_1 \leftarrow 0$

Verification of Extended VASS

REACHABILITY

Instance: an EVASS and two configurations $p(\mathbf{x})$, $q(\mathbf{y})$.

Question: is $p(\mathbf{x}) \xrightarrow{*} q(\mathbf{y})$?

COVERABILITY

Instance: an EVASS and two configurations $p(\mathbf{x})$, $q(\mathbf{y})$.

Question: is $p(\mathbf{x}) \xrightarrow{*} q(\mathbf{z})$ for some $\mathbf{z} \geq \mathbf{y}$?

BOUNDEDNESS

Instance: an EVASS and a configuration $p(\mathbf{x})$.

Question: is $\{q(\mathbf{y}) \mid p(\mathbf{x}) \xrightarrow{*} q(\mathbf{y})\}$ finite ?

Verification of Extended VASS — Some Known Results

	Boundedness	Coverability	Reachability
d -dim VASS	EXPSpace-c		Dec
$T(1)$	Dec		
$T(\star)$	Und ($d \geq 2$)		
$R(1)$	Dec ¹		
$R(1), R(2)$	Dec	Dec ²	Und ($d \geq 3$)
$R(\star)$	Und ($d \geq 3$)	Dec ²	Und ($d \geq 3$)
$Tr(1)$	Dec ¹		
$Tr(\star)$	Dec ²		Und ($d \geq 3$)

[1] Resets $R(i)$ and transfers $Tr(i, j)$ can be simulated by tests $T(i)$


[2] By general results on well-structured transition systems

Verification of 2-dim Extended VASS

REACHABILITY, COVERABILITY, BOUNDEDNESS, ...

Is $post^*$ / pre^* / $\overset{*}{\rightarrow}$ Presburger-definable? If so can we compute it?

$FO(\mathbb{N}, +)$



Verification of 2-dim Extended VASS

REACHABILITY, COVERABILITY, BOUNDEDNESS, ...

Is $post^* / pre^* / \xrightarrow{*}$ Presburger-definable? If so can we compute it?


$FO(\mathbb{N}, +)$



Classes $T_I R_J Tr_K$ with $I, J, K \subseteq \{1, 2\}$

- I : counters that can be tested for zero
- J : counters that can be reset
- K : counters that can be transferred from

Verification of 2-dim Extended VASS — State of Art




Reachability undecidable
[Minsky 1967]

2-dim VASS

*post** / *pre** eff. Presb.
[Hopcroft, Pansiot 1979]

Verification of 2-dim Extended VASS — State of Art



Reachability undecidable
[Minsky 1967]

$T_1R_1Tr_1$



T_1


2-dim VASS

*post** / *pre** eff. Presb.


*post** / *pre** eff. Presb.
[Hopcroft, Pansiot 1979]

Verification of 2-dim Extended VASS — State of Art

Reachability undecidable
[Minsky 1967]



*post** Presb.
*pre** eff. Presb.
[Finkel, Sutre 2000]




*post** / *pre** eff. Presb.

2-dim VASS


*post** / *pre** eff. Presb.
[Hopcroft, Pansiot 1979]

Verification of 2-dim Extended VASS — State of Art

Reachability undecidable
[Minsky 1967]




*post** Presb.
*pre** eff. Presb.
[Finkel, Sutre 2000]



*post**/*pre** eff. Presb.
[Finkel, Sutre 2000]

*post**/*pre** eff. Presb.
[Hopcroft, Pansiot 1979]

Verification of 2-dim Extended VASS — State of Art



Reachability undecidable
[Minsky 1967]

$T_1R_{1,2}Tr_1$

T_1R_2

*post** Presb.
*pre** eff. Presb.
[Finkel, Sutre 2000]




*post**/*pre** eff. Presb.
[Finkel, Sutre 2000]


2-dim VASS

*post**/*pre** eff. Presb.
[Hopcroft, Pansiot 1979]

Verification of 2-dim Extended VASS — State of Art



Reachability undecidable
[Minsky 1967]




$post^*$ Presb.
 pre^* eff. Presb.
[Finkel, Sutre 2000]

$post^*/pre^*$ eff. Presb.
[Finkel, Sutre 2000]


\rightarrow^* eff. Presb.
[Leroux, Sutre 2004]

Verification of 2-dim Extended VASS — State of Art




Reachability undecidable
[Minsky 1967]

- 2-dim VASS reachability problem:
 - ▶ PSPACE-complete with integers in binary [Blondin, Finkel, Göller, Haase, McKenzie 2015]
 - ▶ NL-complete with integers in unary [Englert, Lazic, Totzke 2016]
- d -dim Hierarchically-Extended VASS:
 - ▶ decidability status of reachability, coverability, termination and deadlock-freedom [Akshay, Chakraborty, Das, Jagannath, Sandeep 2017]



* → eff. Presb.
[Leroux, Sutre 2004]

Verification of 2-dim Extended VASS — State of Art



Main Contribution of the Paper

$\text{TRVASS} = \mathbf{T}_1\mathbf{R}_2 = 2\text{-dim VASS extended with } T(1) \text{ and } R(2)$

Theorem


The reachability relation of a TRVASS is effectively Presburger-definable.

Main Contribution of the Paper

TRVASS = $\mathbf{T}_1\mathbf{R}_2$ = 2-dim VASS extended with $T(1)$ and $R(2)$

Theorem

The reachability relation of a TRVASS is effectively Presburger-definable.




Main Contribution of the Paper


TRVASS = $\mathbf{T}_1\mathbf{R}_2$ = 2-dim VASS extended with $T(1)$ and $R(2)$

Theorem

The reachability relation of a TRVASS is effectively Presburger-definable.



A Crucial Observation on Runs of TRVASS




$$\Sigma = \mathbf{A} \cup \{T, R\}$$

$$\mathbf{A} = \{(1,0), (-2,4), (1,-1)\}$$

Decomposition of runs from p in the example:

$$p(x_{\text{init}}, y_{\text{init}}) \xrightarrow{\mathbf{A}^*} \xrightarrow{T} r(0, y_1) \xrightarrow{\mathbf{A}^*} \xrightarrow{R} p(x_2, 0) \xrightarrow{\mathbf{A}^*} \xrightarrow{T} r(0, y_3) \cdots$$

A Crucial Observation on Runs of TRVASS



$$\Sigma = \mathbf{A} \cup \{T, R\}$$

$$\mathbf{A} = \{(1, 0), (-2, 4), (1, -1)\}$$

Decomposition of runs from p in the example:

$$p(x_{\text{init}}, y_{\text{init}}) \xrightarrow{\mathbf{A}^*} \xrightarrow{T} r(0, y_1) \xrightarrow{\mathbf{A}^*} \xrightarrow{R} p(x_2, 0) \xrightarrow{\mathbf{A}^*} \xrightarrow{T} r(0, y_3) \cdots$$

Decomposition of runs in general:

$$c_{\text{init}} \xrightarrow{\mathbf{A}^*} \xrightarrow{T|R} c_1 \xrightarrow{\mathbf{A}^*} \xrightarrow{T|R} c_2 \cdots \xrightarrow{\mathbf{A}^*} \xrightarrow{T|R} c_k \xrightarrow{\mathbf{A}^*} c_{\text{final}}$$

where **at least one counter is zero** in c_i

Presburger (One-Counter) Automata

Definition

A **Presburger automaton** is a pair $\langle Q, \Delta \rangle$ where

- Q : finite set of **states**
- $\Delta \subseteq Q \times 2_{\text{Presb}}^{\mathbb{N} \times \mathbb{N}} \times Q$: finite set of **transitions**

Presburger-definable binary relations $S \subseteq \mathbb{N} \times \mathbb{N}$

Configurations: $q(x)$ with $q \in Q$ and $x \in \mathbb{N}$

Steps:

$$p(x) \rightarrow q(y) \quad \text{iff} \quad \exists (p \xrightarrow{S} q) \in \Delta : (x, y) \in S$$

Presburger (One-Counter) Automata

Definition

A **Presburger automaton** is a pair $\langle Q, \Delta \rangle$ where

- Q : finite set of **states**
- $\Delta \subseteq Q \times 2_{\text{Presb}}^{\mathbb{N} \times \mathbb{N}} \times Q$: finite set of **transitions**

Presburger-definable binary relations $S \subseteq \mathbb{N} \times \mathbb{N}$

Configurations: $q(x)$ with $q \in Q$ and $x \in \mathbb{N}$

Steps:

$$p(x) \rightarrow q(y) \quad \text{iff} \quad \exists (p \xrightarrow{S} q) \in \Delta : (x, y) \in S$$

⇨ Reachability is undecidable for Presburger automata in general

From TRVASS to Presburger Automata

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$


⇒ Summarizes runs of the TRVASS between two extended actions

States of \mathcal{P} :

$$\{q^T, q^R \mid q \in Q\}$$

$q^T(n) \approx q(0, n)$ $q^R(n) \approx q(n, 0)$

Transitions of \mathcal{P} :



$$S_{TT}(m, n) \stackrel{\text{def}}{\Leftrightarrow} p(0, m) \xrightarrow{\mathbf{A}^*T} q(0, n)$$

$$S_{RT}(m, n) \stackrel{\text{def}}{\Leftrightarrow} p(m, 0) \xrightarrow{\mathbf{A}^*T} q(0, n)$$

$$S_{TR}(m, n) \stackrel{\text{def}}{\Leftrightarrow} p(0, m) \xrightarrow{\mathbf{A}^*R} q(n, 0)$$

$$S_{RR}(m, n) \stackrel{\text{def}}{\Leftrightarrow} p(m, 0) \xrightarrow{\mathbf{A}^*R} q(n, 0)$$

From TRVASS to Presburger Automata

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$


⇨ Summarizes runs of the TRVASS between two extended actions

States of \mathcal{P} :

$$\{q^T, q^R \mid q \in Q\}$$

$q^T(n) \approx q(0, n)$ $q^R(n) \approx q(n, 0)$

Transitions of \mathcal{P} :



$$S_{TT}(m, n) \stackrel{\text{def}}{\Leftrightarrow} p(0, m) \xrightarrow{\mathbf{A}^* T} q(0, n)$$

Theorem ([Leroux, Sutre 2004])


The reachability relation $\xrightarrow{\mathbf{A}^*}$ is effectively Presburger-definable.

From TRVASS to Presburger Automata — Continued


Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

⇒ Summarizes runs of the TRVASS between two extended actions

\mathcal{V}



\mathcal{P} limited to p^R and r^T



If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

From TRVASS to Presburger Automata — Continued

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

⇒ Summarizes runs of the TRVASS between two extended actions

If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

From TRVASS to Presburger Automata — Continued

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

⇨ Summarizes runs of the TRVASS between two extended actions

If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

$$\xrightarrow{*}_{\mathcal{V}} = \xrightarrow{\mathbf{A}^*} \cup \xrightarrow{\mathbf{A}^* \{T,R\} \mathbf{A}^*} \cup \xrightarrow{\mathbf{A}^* \{T,R\} \Sigma^* \{T,R\} \mathbf{A}^*}$$

From TRVASS to Presburger Automata — Continued

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

⇨ Summarizes runs of the TRVASS between two extended actions

If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

$$\xrightarrow{*}_{\mathcal{V}} = \xrightarrow{\mathbf{A}^*} \cup \xrightarrow{\mathbf{A}^* \{T,R\} \mathbf{A}^*} \cup \xrightarrow{\mathbf{A}^* \{T,R\} \Sigma^* \{T,R\} \mathbf{A}^*}$$

$p(x_1, x_2) \xrightarrow{\mathbf{A}^* T \Sigma^* R \mathbf{A}^*} q(y_1, y_2)$ iff there exist $r, s \in Q$ and $m, n \in \mathbb{N}$ such that


$$p(x_1, x_2) \xrightarrow{\mathbf{A}^* T} r(0, m) \wedge r^T(m) \xrightarrow{*}_{\mathcal{P}} s^R(n) \wedge s(n, 0) \xrightarrow{\mathbf{A}^*} q(y_1, y_2)$$

Diagonal Presburger-Definable Relations

Definition

A relation $S \subseteq \mathbb{N} \times \mathbb{N}$ is **diagonal** if

$$x S y \Rightarrow (x + c) S (y + c)$$



$$\underbrace{p(0, m) \xrightarrow{\mathbf{A}^*T} q(0, n)}_{S_{TT}} \text{ and } \underbrace{p(m, 0) \xrightarrow{\mathbf{A}^*R} q(n, 0)}_{S_{RR}} \text{ are diagonal}$$



Theorem

*Diagonal Presburger-definable relations are effectively closed under union, intersection, composition and **transitive closure**.*

Diagonal Presburger-Definable Relations — Example

$$x S y \stackrel{\text{def}}{\Leftrightarrow} x \leq y \wedge y \leq 2x$$

$$x S^+ y \Leftrightarrow x \leq y \wedge (x = 0 \Leftrightarrow y = 0)$$



Diagonal Presburger-Definable Relations — Proof

$$I_S = \{x \mid \exists y > x : x S y\}$$

$$D_S = \{y \mid \exists x > y : x S y\}$$

$$\alpha = \min\{\delta > 0 \mid \forall x \in I_S : (x, x + \delta) \in S\} \quad (0 \text{ if } I_S = \emptyset)$$

$$\beta = \min\{\delta > 0 \mid \forall y \in D_S : (y + \delta, y) \in S\} \quad (0 \text{ if } D_S = \emptyset)$$

$$\text{Inc}_S(x, y) \stackrel{\text{def}}{\iff} (x = y) \vee (x \in I_S \wedge y \in x + \mathbb{N}\alpha)$$

$$\text{Dec}_S(x, y) \stackrel{\text{def}}{\iff} (x = y) \vee (y \in D_S \wedge x \in y + \mathbb{N}\beta)$$

Lemma


If $S \subseteq \mathbb{N} \times \mathbb{N}$ is diagonal then $S^+ = \text{Inc}_S \cdot (S \cup \dots \cup S^{\alpha+\beta+1}) \cdot \text{Dec}_S$.

Horizontal Presburger-Definable Relations

Definition

A relation $S \subseteq \mathbb{N} \times \mathbb{N}$ is **horizontal** if

$$x S y \Rightarrow (x + c) S y$$



$\underbrace{p(0, m) \xrightarrow{A^*R} q(n, 0)}_{S_{TR}}$ is horizontal



Theorem

*Horizontal Presburger-definable relations are effectively closed under union, intersection, composition and **transitive closure**.*

Horizontal Presburger-Definable Relations — Example

$$x S y \stackrel{\text{def}}{\Leftrightarrow} y \in 2\mathbb{N} \wedge y \leq 2x$$

$$x S^+ y \Leftrightarrow y \in 2\mathbb{N} \wedge (x = 0 \Rightarrow y = 0)$$



Lemma

If $S \subseteq \mathbb{N} \times \mathbb{N}$ is horizontal then $x S^+ y$ iff there exists z such that

$$z S y \wedge \forall u \in \{x, \dots, z-1\}, \exists v > u : u S v$$

Assume $x = x_0 S x_1 S \dots S x_k = y$.

If $x_{i-1} \geq x_i$ then $x_{i-1} S x_{i+1}$. So we may suppose w.l.o.g. that

$$x_0 < x_1 < \dots < x_{k-1}$$

Hence $u S x_i$ for all $u \in \{x_{i-1}, \dots, x_i - 1\}$ and $0 < i < k$.

So for all $u \in \{x_0, \dots, x_{k-1} - 1\}$, there is $v > u$ with $u S v$.

Take $z = x_{k-1}$.

Lemma

If $S \subseteq \mathbb{N} \times \mathbb{N}$ is horizontal then $x S^+ y$ iff there exists z such that

$$z S y \wedge \forall u \in \{x, \dots, z-1\}, \exists v > u : u S v$$

Assume $z S y$ and for all $u \in \{x, \dots, z-1\}$, there is $v > u$ with $u S v$.

If $x \geq z$ then $x S y$. Otherwise, there exists $x_1 > x$ with $x S x_1$.

Repeat this process to build $x < x_1 < \dots < x_k$ with $x S x_1 S \dots S x_k$ and $x_k \geq z$.


Since $z S y$, we get $x_k S y$.

Shallow Presburger Automata

Definition

A Presburger automaton is **shallow** if every cycle contains

only diagonal transitions or **an horizontal** transition




Theorem

The reachability relation of a shallow Presburger automaton is effectively Presburger-definable.

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions


Base case: every SCC contains only diagonal transitions



Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Base case: every SCC contains only diagonal transitions




Diagonal Presburger-definable relations effectively closed under union, composition and reflexive-transitive closure

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Base case: every SCC contains only diagonal transitions




Diagonal Presburger-definable relations effectively closed under union, composition and reflexive-transitive closure

So $\xrightarrow{*}$ is effectively Presburger-definable within each SCC

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Induction step: pick an horizontal transition $p \xrightarrow{H} q$




A run from s to t

- either never takes $p \xrightarrow{H} q$
- or takes $p \xrightarrow{H} q$ at least once

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Induction step: pick an horizontal transition $p \xrightarrow{H} q$



A run from s to t

- either never takes $p \xrightarrow{H} q$
- or takes $p \xrightarrow{H} q$ at least once

$m R_1 n \stackrel{\text{def}}{\Leftrightarrow} s(m) \xrightarrow{*} p(n)$ in the Presburger automata without $p \xrightarrow{H} q$


R_1, R_2, R_3, R_4 are effectively Presburger-definable by Ind. Hyp.

(Removing transitions preserves shallowness.)

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Induction step: pick an horizontal transition $p \xrightarrow{H} q$



A run from s to t

- either never takes $p \xrightarrow{H} q$
- or takes $p \xrightarrow{H} q$ at least once


$$s(m) \xrightarrow{*} t(n)$$

$$\Leftrightarrow m R_4 n \vee \exists m', n' : m R_1 m' \wedge m' ((H \cdot R_2)^* \cdot H) n' \wedge n' R_3 n$$

Shallow Presburger Automata — Proof

By induction on the number of horizontal transitions

Induction step: pick an horizontal transition $p \xrightarrow{H} q$



A run from s to t

- either never takes $p \xrightarrow{H} q$
- or takes $p \xrightarrow{H} q$ at least once

$$s(m) \xrightarrow{*} t(n)$$

$$\Leftrightarrow m R_4 n \vee \exists m', n' : m R_1 m' \wedge m' ((H \cdot R_2)^* \cdot H) n' \wedge n' R_3 n$$

$H \cdot R_2$ is horizontal, so $(H \cdot R_2)^*$ is effectively Presburger-definable

Wrap-Up

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$


If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

Wrap-Up

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

If $\xrightarrow{*}_{\mathcal{P}}$ is effectively Presburger-definable then so is $\xrightarrow{*}_{\mathcal{V}}$

Transitions of \mathcal{P} :



$S_{TT}(m, n)$: diagonal

$S_{RT}(m, n)$: ordinary

$S_{TR}(m, n)$: horizontal


$S_{RR}(m, n)$: diagonal

Wrap-Up

Presburger automaton \mathcal{P} associated to a TRVASS $\mathcal{V} = \langle Q, \Sigma, \Delta \rangle$

If $\rightarrow_{\mathcal{P}}^*$ is effectively Presburger-definable then so is $\rightarrow_{\mathcal{V}}^*$

Transitions of \mathcal{P} :



$S_{TT}(m, n)$: diagonal
 $S_{RT}(m, n)$: ordinary
 $S_{TR}(m, n)$: horizontal
 $S_{RR}(m, n)$: diagonal

\mathcal{P} is shallow so $\rightarrow_{\mathcal{P}}^*$ is effectively Presburger-definable

Summary

<i>Class</i>	<i>Post*</i>	$\xrightarrow{*}$
$\mathbf{T}_1\mathbf{Tr}_2 \simeq \mathbf{T}_{1,2} \simeq \mathbf{T}_{1,2}\mathbf{R}_{1,2}\mathbf{Tr}_{1,2}$	Reachability, ... undecidable	
TRVASS = $\mathbf{T}_1\mathbf{R}_2 \simeq \mathbf{T}_1\mathbf{R}_{1,2}\mathbf{Tr}_1$	Eff. Presburger	Eff. Presburger
$\mathbf{R}_{1,2}\mathbf{Tr}_1 \simeq \mathbf{R}_{1,2}\mathbf{Tr}_{1,2}$	Eff. Presburger	Eff. Presburger
$\mathbf{T}_1 \simeq \mathbf{T}_1\mathbf{R}_1\mathbf{Tr}_1$	Eff. Presburger	Eff. Presburger
2-dim VASS	Eff. Presburger	Eff. Presburger

- Simple proof that unifies and **generalizes** all existing results
- $Post^*$ is effectively Presburger-definable for TRVASS
 - ▶ Boundedness is decidable

Relies on the effective Presburger-definability of $\xrightarrow{*}$ for 2-dim VASS
[Leroux, Sutre 2004]

- Boundedness for d -dim TRVASS ($d \geq 3$)
 - ▶ Decidable for d -dim RRVASS [Dufourd, Jančar, Schnoebelen 1999]
- Complexity of reachability for TRVASS
 - ▶ PSPACE-complete for 2-dim VASS in binary [Blondin, Finkel, Göller, Haase, McKenzie 2015]
 - ▶ NL-complete for 2-dim VASS in unary [Englert, Lazic, Totzke 2016]
- Reachability for 1-dim Pushdown VASS
 - ▶ Coverability is decidable [Leroux, Sutre, Totzke 2015]

Open Problems

- Boundedness for d -dim TRVASS ($d \geq 3$)
 - ▶ Decidable for d -dim RRVASS [Dufourd, Jančar, Schnoebelen 1999]
- Complexity of reachability for TRVASS
 - ▶ PSPACE-complete for 2-dim VASS in binary [Blondin, Finkel, Göller, Haase, McKenzie 2015]
 - ▶ NL-complete for 2-dim VASS in unary [Englert, Lazic, Totzke 2016]
- Reachability for 1-dim Pushdown VASS
 - ▶ Coverability is decidable [Leroux, Sutre, Totzke 2015]

Thank You!