



L I F C



IWJPDC'04

UNIVERSITÉ DE FRANCHE-COMTÉ



Combination of Java and asynchronism for the Grid : a comparative study based on a parallel power method.



Jacques Bahi, Stephane Domas, Kamel Mazouzi
bahi, sdomas, mazouzi@iut-bm.univ-fcomte.fr

Young Team AND



L I F C



Overview

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

- ◉ Distributed computing and its problems,
- ◉ Asynchronous vs. synchronous iterative algorithms,
- ◉ Jace : an environment for asynchronous algorithms,
- ◉ Parallel Power Method,
- ◉ Experiments,
- ◉ Conclusion.



L I F C



Distributed computing

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

🌀 Classical hardware architecture:

- clusters or LANs distributed over different geographical sites,
- shared and variable bandwidth between sites.

🌀 Classical software framework :

- MPI-like environments,
- meta-computing environments (GLOBUS, DIET,...).



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

Distributed computing : problems

螺旋 Network :

- restricted accesses (firewall, private IPs, ...),
- costly synchronizations,
- bandwidth between sites easily overloaded.

螺旋 Heterogeneity:

- load balancing often necessary,
- different communication/computation libraries on sites,
- fastidious compilation and installation.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

Distributed computing : classical solutions

- 🌀 Network : dedicated high speed network.
 - expensive.
- 🌀 Heterogeneity : meta-computing environment.
 - a single site is chosen for each execution,
 - restrictions on the executed code,
 - user has little control over execution,
 - heavy environments.

These solutions adapt the Grid to existing works !



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



Distributed computing : innovating solutions

- ◉ Avoid synchronizations :
 - less bandwidth overload,
 - less idle times.
- ◉ Use a dedicated Java environment.
 - 100% portable,
 - lightweight environment,
 - user can execute any code he develops.

Asynchronous algorithms implemented with Jace environment provide all of these !





L I F C

Synchronous vs. Asynchronous

UNIVERSITÉ DE FRANCHE-COMTÉ



For an iterative algorithm :



FRE 2661



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



AIAC algorithms : summary (1)

No synchronization phases :

- no gather-scatter to test convergence at the end of each iteration,
- exclusive use of non blocking communications.



Message incoming tolerance :

- no idle time to wait for needed messages,
- messages can be delayed or even lost,
- discarding "too old" messages is possible.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



AIAC algorithms : summary (2)


螺旋 No idle times between iterations :

- at each time, processors may compute different iterations,
- heterogeneous workload has less impact.

螺旋 Convergence under some conditions :

- satisfied for a large class of scientific applications,
- convergence acceleration mechanisms.

⇒ perfect for grid/distributed computing.



L I F C



Jace

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

- Designed to manage communications for asynchronous algorithms,
- Builds a parallel virtual machine by connecting a set of heterogeneous and distant machines,
- Provides a simple programming interface to develop message passing codes.
- Jace is composed of :
 - Daemon,
 - Task,
 - Spawner.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



Jace Architecture : Daemon

- Launched on each computing node,
- Provides authentication and task execution,
- Each Daemon can run several tasks,
- Manages communications :
 - messages are sent/received via RMI,
 - multi-threaded to implement non blocking communications,
 - older occurrences of the same message are **automatically** crushed.



L I F C



Jace Architecture : Task

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

② The Task class is :

- the computing unit,
- a thread rather than a process (**unlike MPI**),
- the programming interface to access to the communication layer (non-blocking send/receive, barrier,...).

③ User's Task :

- inherits from the Task Class,
- defines a run method containing the computing code.



L I F C



Jace : Raw Performances

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

Length in Kb	Jace	JPVM	MPI
0	7	8	0.11
10	8	12	2.23
100	24	27	21
500	108	113	100
800	183	211	170
1024	215	252	202

Table 1: Results of Ping-pong in ms



L I F C



Jace : Current Extensions

UNIVERSITÉ DE FRANCHE-COMTÉ



- ◉ Hierarchical communication scheme :
 - access LANs or clusters with private addresses,
 - bypass firewall.
- ◉ Load balancing :
 - migrating user's tasks within a site,
 - "smart" spawner.



FRE 2661



L I F C



Parallel Power Method (1)

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

○ Computes :

- λ_1 : the eigenvalue of largest modulus,
- its associated eigenvector.

○ Assumptions :

- $|\lambda_1|$ is a single eigenvalue,
- p computing tasks,
- $A_{n \times n}$ is cut in p horizontal strips.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



Parallel Power Method (2)

receive A^{me} and x_0

$k = 1$

do

$$y_k^{me} = A^{me} \cdot x_{k-1}$$

send y_k^{me} to all other processors.

receive y_k^i for $i = 0, \dots, p - 1$ and $i \neq me$

$$\alpha_k = \|y_k\|$$

$$x_k = \frac{y_k}{\alpha_k}$$

test global convergence

receive stop/continue message.

$$k+ = 1$$

while no stop message is received



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661



Experiments

Framework :

- 8 heterogeneous machines,
- 3 distant sites,
- heterogeneous bandwidth (ADSL, 10Mb, 100Mb).

Tests :

- sparse stochastic matrix of 4096 order.
- comparison between synchronous and asynchronous versions,
- increasing precision,
- with and without static load balancing.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

Experiments : no load balancing

precision	siac	aiac	ratio
10^{-3}	82 (18)	60 (43 - 239)	1.36
10^{-4}	136 (30)	92 (67 - 357)	1.47
10^{-5}	196 (42)	113 (82 - 429)	1.73
10^{-6}	255 (55)	132 (95 - 536)	1.93
10^{-7}	300 (67)	170 (116 - 641)	1.76

Table 2: Comparison between synchronous and asynchronous versions without load balancing.



L I F C

UNIVERSITÉ DE FRANCHE-COMTÉ



Experiments : static load balancing

precision	siac	aiac	ratio
10^{-3}	86 (18)	28 (53 - 98)	3.07
10^{-4}	140 (30)	54 (84 - 203)	2.59
10^{-5}	196 (42)	74 (147 - 266)	2.64
10^{-6}	258 (55)	91 (174 - 313)	2.83
10^{-7}	316 (67)	115 (225 - 412)	2.74

Table 3: Comparison between synchronous and asynchronous versions with static load-balancing.



L I F C



Experiments : Summary

UNIVERSITÉ DE FRANCHE-COMTÉ



- 🌀 AIAC implies more iterations,
- 🌀 AIAC is more efficient if synchronous version does a significant number of iterations,
- 🌀 static load balancing has a real impact on AIAC,
- 🌀 results greatly depend on the ratio computation/communication.



FRE 2661



L I F C



Conclusion

UNIVERSITÉ DE FRANCHE-COMTÉ



FRE 2661

🌀 Asynchronism + Java :

- a new environment : Jace,
- an innovating way to adapt scientific computation to the Grid,
- portable codes,
- efficient executions on heterogeneous multi-sites architectures.

🌀 In the future:

- a general study of AIAC algorithms using Jace,
- extending Jace specifications to integrate classical grid services.