

# A multivariate interlace polynomial

Bruno Courcelle

LaBRI, Université Bordeaux 1 and CNRS

## General objectives :

Logical descriptions of graph polynomials

Application to their computations

Systematic construction of recursive definitions

**Here** : the multivariate *Interlace polynomial*

Full article on ArXiv and HAL.

## Multivariate polynomials

*Example:* Sokal's multivariate version of Tutte's two-variable polynomial

For a graph  $G=(V,E)$  :

$$Z(G) = \sum_{A \subseteq E} u^{k(G[A])} \prod_{e \in A} x_e$$

where  $G[A]$  is the subgraph of  $G$  with set of vertices  $V$  and set of edges  $A$ ,

$k(G[A])$  is the number of its connected components,

$x_e$  is an indeterminate associated with each  $e$  in  $E$ ,

$u$  is an "ordinary indeterminate".

Multivariate polynomials not only count *configurations* (spanning trees, colorings,...) but they enumerate them (with associated values).

*Logical view : typical form :*

$$P(G) = \sum_{\varphi(A,B)} x_A y_B u^{f(A,B)}$$

$A, B$  sets of vertices or edges

satisfying condition  $\varphi(A, B)$

$f(A, B)$  nonnegative integer function of  $A, B$ ,

$x_A$  and  $y_B$  denote

$$\prod_{a \in A} x_a, \quad \prod_{a \in B} y_a$$

## Logical expression of Condition $\varphi$

Second-order logic (SO) : very (too) powerful

= First-order logic with set and relation quantifications.

Monadic second-order logic (MS) : quite powerful, very good algorithmic properties,

= First-order logic with set quantifications (only).

### Typical properties :

MS :  $X$  is a set of edges defining a spanning forest, or  $X$  is a set of vertices inducing a connected component.

SO not MS : two sets  $X$  and  $Y$  are in bijection.

Example of MS formula :

The induced subgraph  $G[X]$  is not connected

$$\begin{aligned} \exists Y \cdot [ & \exists x \cdot (x \in X \wedge x \in Y) \wedge \exists y (y \in X \wedge y \notin Y) \wedge \\ & \forall x, y \cdot (x \in X \wedge y \in X \wedge A(x, y) \\ & \Rightarrow \{(x \in Y \wedge y \in Y) \vee (x \notin Y \wedge y \notin Y)\})]. \end{aligned}$$

where  $A(x, y)$  is the adjacency relation.

Logical expression of functions with values in  $\mathbf{N}$  in

$$P(G) = \sum_{\varphi(A,B)} x_A y_B u^{f(A,B)}$$

*If*  $f(A,B) = |C|$  for a **unique set**  $C$  satisfying  $\psi(A,B,C)$

*then*  $P = P' [ u_c \leftarrow u ]$  (**substitution**) where

$$P'(G) = \sum_{\psi(A,B,C)} x_A y_B u_C$$

*Example* (for Sokal's polynomial) :

$k(G[A])$  = number of connected components is defined as  $|C|$  where :

$\psi(A,C) \Leftrightarrow C$  is the set of vertices which are **minimal** in each connected component of the graph  $(V,A)$  ; "minimal" is with respect to an arbitrary linear ordering of  $V$ . (sets  $C$  depend on this order but not  $|C|$ ).

The polynomial  $Z(G)$  can thus be rewritten as :

$$\begin{aligned} Z(G) &= \sum_{A \subseteq E} x_A u^{k(G[A])} \\ &= \left( \sum_{\psi(A,C)} x_A u_C \right) [u_c := u \quad \text{all } c \in V] \end{aligned}$$

## Why Monadic Second-order logic ?

Polynomials and *truncations of multivariate MS-definable* polynomials can be computed in polynomial time for input graphs of *bounded tree-width or clique-width*.

This result covers such results for (*nonmultivariate*) :

- 1) Tutte polynomial for graphs of bounded tree-width (Noble, Andrzejak, 1998)
- 2) Interlace polynomial for distance-hereditary graphs (of clique-width 3) (Ellis-Monaghan, Sarmiento, 2006)



## Interlace polynomials

Several (incompatible ) *interlace* polynomials by :  
Arratia, Bollobas and Sorkin (2 articles in 2004), and  
Aigner and van der Holst (2004).

### *Motivations :*

- Counting partitions into  $k$  circuits (Las Vergnas, Martin)
- Counting the number of Eulerian trails in 4-regular graphs
- Related to Kauffman's polynomial of link diagrams.

*This communication :*

- a common **multivariate interlace polynomial**,
- generalizing all the existing ones,
- **MS-definable** (hence truncations are poly-time computable for graphs of bounded clique-width),
- with a **recursive definition** from which the existing ones can be established.

Only bounded portions can be evaluated in polynomial time. The full computation is necessarily exponential because of the size of the result.

## Description of the new animal (for Janos's Zoo).

Configurations : sets  $A$  of vertices ;

Their values based on the *rank* of the induced subgraph.

To generalize the polynomial by Aigner, we put also in a configuration a set  $B$  of vertices for "toggling loops": if a vertex in  $B$  has no loop, we add one ; if it has a loop, we delete it, giving graph  $G \nabla B$

Ranks of adjacency matrices are over  $\text{GF}(2)$ .

## The definition

$$B(G) = \sum_{A \cap B = \emptyset} x_A y_B u^{rk(G \nabla B[A \cup B])} v^{n(G \nabla B[A \cup B])}$$

where  $A, B$  range over subsets of  $V$  (vertices)

$rk(H)$  denotes the rank of a graph  $H$ ,

$n(H) = |V| - rk(H)$  denotes the *nullity*.

The existing interlace polynomials are specializations:

$$q(G, x, y) = \sum_{A \subseteq E} (x - 1)^{rk(G[A])} (y - 1)^{n(G[A])}$$

$= \sigma(B(G))$  where  $\sigma$  is the substitution

$$[u := x - 1; v := y - 1; x_a := 1, y_a := 0 \quad \text{all } a \in V],$$

$$Q(G, x) = \sum_{A \cap B = \emptyset} (x - 2)^{n(G \nabla B[A \cup B])}$$

idem with  $\sigma = [u := 1; v := x - 2; x_a := y_a := 1 \quad \text{all } a \in V]$ .

## B(G) is MS-definable

Because  $rk(G[A]) = |C|$  if  $C$  is a maximal subset of  $A$  with associated row vectors in the adjacency matrix of  $G[A]$  that are independent.

This is expressible in MS logic augmented with the **Even cardinality set predicate** :  $Even(X)$

This extension satisfies all good algorithmic properties of MS logic.

**The recursive definition** : For every vertex  $a$  :

$$B(\emptyset) = 1$$

$$B(G) = (1 + z_a v + w_a u) B(G - a) \quad \text{if } N(G, a) = \emptyset ,$$

$$\begin{aligned} B(G) = z_b u^2 \{ & z_a B(G^{ab} - a - b) + w_a B((G^a)^b - a - b) \} \\ & + w_b u \{ B(G^b - b) - B(G^b - a - b) \} \\ & + B(G - a) + B(G - b) - B(G - a - b). \end{aligned}$$

if  $b \in N(G, a)$  (set of neighbours of  $a$ ).

We use "metavariables", for each  $c$  in  $V$  :

$$z_c = x_c \quad \text{and} \quad w_c = y_c \quad \text{if } c \text{ is not a loop,}$$

$$z_c = y_c \quad \text{and} \quad w_c = x_c \quad \text{if } c \text{ is a loop.}$$

This definition involves the following graph transformations :

$G^a$  : **local complementation at  $a$**  : toggles edges and loops in the neighbourhood of  $a$  ;

$G^{ab}$  : **pivoting edge  $ab$** : toggles edges between  $N(G,a)-N(G,b)$  ,  $N(G,b)-N(G,a)$  and  $N(G,a) \cap N(G,b)$  ;

$G-a$  : deletion of vertex  $a$

Its determination is based on the Lemma (ABS+C):

- (1)  $rk(G) = 1 + rk(G^a - a)$  if  $a \in Loops(G)$  ;
- (2)  $rk(G) = 2 + rk(G^{ab} - a - b)$  if  $a - b$  ;
- (3)  $rk(G - a) = rk(G^{ab} - a)$  if  $a - b$ ;
- (4)  $rk(G) = 2 + rk((G^a)^b - a - b) = 1 + rk(G^{ab} - b)$   
if  $a^\ell - b$  .

We can derive the known recursive definitions, sometimes with the necessity of proving nontrivial properties.

**Property:** For every graph  $G$  and vertex  $a$  the polynomial  $B(G) - B(G - a)$  has positive coefficients.



## Recursive definitions of $q(G,x,y)$ and $Q(G,x)$

(q1)  $q(G) = y^n$  if  $G = n$  isolated non-looped vertices,

(q2)  $q(G) = (x - 1)q(G^a - a) + q(G - a)$  if  $a$  loop, isolated or not,

(q3)  $q(G) = (x - 1)^2 q(G^{ab} - a - b) +$   
 $+ q(G - a) + q(G - b) - q(G - a - b)$  if  $a-b$

It is not the one of [ABS].; they replace (q3) by :

(q'3)  $q(G) = x(x - 2)q(G^{ab} - a - b) +$   
 $+ q(G - a) + q(G^{ab} - b)$

(Q1)  $Q(\emptyset) = 1$

(Q2)  $Q(G) = x \cdot Q(G - a)$  if  $N(G, a) = \emptyset$

(Q3)  $Q(G) = Q(G^{ab} - a - b) + Q((G^a)^b - a - b)$   
 $+ Q(G^b - b) - Q(G^b - a - b)$   
 $+ Q(G - a) + Q(G - b) - Q(G - a - b)$  if  $b \in N(G, a)$

(Q'3)  $Q(G) = Q(G - b) + Q(G * b - b) + Q(G^{ab} - a)$  if  $b \in N(G, a)$

where  $G * b = G^b \nabla N(G, b)$

## Computing $B(G)$ and multivariate polynomials

Such polynomials have exponential size.

We may ask for a polynomial time **computation**

(not an evaluation for particular values) of the

**d-truncation** of  $B(G)$ , i.e., of its part limited to the monomials of **quasi-degree** at most **d** (number of distinct **indexed indeterminates**; indexed by vertices or edges).

Because  $B(G)$  is MS-definable, this is possible for graphs of bounded clique-width. This includes cographs and distance-hereditary graphs.

**Theorem** : For each  $k$ , the following polynomials are computable for graphs  $G$  of **clique-width**  $< k$  :

**d-truncation of  $B(G)$**  in time  $O(n^{3d+O(1)})$ ,

**$q(G)$**  in time  $O(n^7)$ ,

**$Q(G)$**  in time  $O(n^3)$ ,

$n$  = number of vertices.

**The basic lemma** (simplified formulation) :

For every MS formula  $\xi$  there exists a finite subset  $\Phi$  of MS formulas containing  $\xi$  such that :

(1) For every  $\varphi$  in  $\Phi$ , for every unary operation  $op$  there exists a formula  $\varphi^{op}$  such that, for every graph  $G$ , for every substitution  $\sigma$  :

$$(\sigma \circ P_\varphi)(op(G)) = (\sigma \circ P_{\varphi^{op}})(G).$$

(2) For every  $\varphi$  in  $\Phi$ , there exists

$$(\theta_1, \dots, \theta_p, \psi_1, \dots, \psi_p) \in \Phi^{2p}$$

such that for every disjoint graphs  $G$  and  $H$ , for every substitution  $\sigma$  :

$$(\sigma \circ P_\varphi)(G \vec{\oplus} H) = \sum_{1 \leq i \leq p} (\sigma \circ P_{\theta_i})(G) \cdot (\sigma \circ P_{\psi_i})(H).$$

**Remark :**

In case of truncations we also have :

$$\sigma(P_\varphi(G \vec{\oplus} H)) \upharpoonright d = \sum_{1 \leq i \leq p} ((\sigma(P_{\theta_i}(G)) \upharpoonright d) \cdot (\sigma(P_{\psi_i}(H)) \upharpoonright d)) \upharpoonright d.$$

**Consequence :** One can compute simultaneously the finitely many polynomials  $\sigma(P_\varphi(G)) \upharpoonright d$  by induction on the structure of a term that describes  $G$  by using the following operations :

ordered disjoint union :  $\vec{\oplus}$

finitely many unary graph operations  
expressible without quantifiers.

This applies to graphs of clique-width at most  $k$ .

## Clique-width

A graph complexity measure like tree-width that yields many **Fixed Parameter Tractable** algorithms, especially for problems expressed in Monadic Second-order logic.

Graphs have vertices labelled in  $\{1,2,\dots,k\}$ .

- (1) For each  $i$  in  $\{1,2,\dots,k\}$ , constants  $\mathbf{i}$  and  $\mathbf{i}^{\text{loop}}$  denote isolated vertices labelled by  $i$ , the second one with a loop.
- (2) For  $i,j$  in  $\{1,2,\dots,k\}$ , the unary function  $\mathit{add}_{i,j}$  adds undirected edges between any two vertices, one labelled by  $i$ , the other by  $j$ .
- (3) The unary function  $\mathit{ren}_{i,j}$  relabels  $i$  into  $j$ .

(4) The binary operation  $\oplus$  makes the union of disjoint copies of its arguments.

The clique-width of a graph is the minimal  $k$  such that this graph can be constructed with these operations.

Cliques have clique-width 2 and unbounded tree-width.

The unary operations are quantifier-free definable.

A variant is used where graphs are linearly ordered and the disjoint union  $\overrightarrow{\oplus}$  concatenates the linear orders.

## References

**R. Arratia, B. Bollobás, G. Sorkin** : The interlace polynomial: a new graph polynomial. J. of Comb. Theory B 92 (2004) 199-233.

**R. Arratia, B. Bollobás, G. Sorkin** : A Two-Variable Interlace Polynomial, Combinatorica 24 (2004) 567-584

**M. Aigner, H. van der Holst**, Interlace polynomials, Linear algebra and applications 377 (2004) 11-30.

**B. Courcelle**, The expression of graph properties and graph transformations in monadic second-order logic, Chapter 5 of the "Handbook of graph grammars and computing by graph transformations, Vol.1: Foundations", G. Rozenberg ed., World Scientific (New-Jersey, London), 1997, pp. 313-400.



**B. Courcelle, J. A. Makowsky, U. Rotics:** On the fixed parameter complexity of graph enumeration problems definable in monadic second-order logic. Discrete Applied Mathematics 108(2001) 23-52

**B. Courcelle, S. Oum,** Vertex-minors, monadic second-order logic and a conjecture by Seese, J. Comb. Theory B 97 (2007) 91-126.

**J.Ellis-Monaghan, I.Sarmiento,** Distance Hereditary Graphs and the Interlace Polynomial, Preprint, arXiv:math.CO/0604088 v1 4 Apr 2006.

**J. Makowsky :** Algorithmic uses of the Feferman--Vaught Theorem, Annals of Pure and Applied Logic 126 (2004) 159--213

**J. Makowsky:** From a Zoo to a Zoology: Descriptive Complexity for Graph Polynomials, In: A. Beckmann, et al. (eds.): Logical Approaches to Computational Barriers, Second Conference on Computability in Europe, LNCS, 3988 (2006) 330-341.

**A. Sokal:** The multivariate Tutte polynomial (alias Potts model) for graphs and matroids. Surveys in Combinatorics (2005) 173-226