

Computing Without Communicating: Ring Exploration by Asynchronous Oblivious Robots

Paola FLOCCHINI¹ David ILCINKAS²
Andrzej PELC³ Nicola SANTORO⁴

¹University of Ottawa, Canada

²CNRS, Université Bordeaux I, France

³Université du Québec en Outaouais, Canada

⁴Carleton University, Canada

OPODIS '07
December 17, 2007

Problem

Model/context

- Team of robots
 - sensing the environment by taking a snapshot of it
 - that do not communicate
 - that are anonymous and oblivious
- Anonymous unoriented rings.

Goal: exploration with stop

- Each node must be visited by at least one robot.
- All robots must stop after finite time.

The Look-Compute-Move cycle

Look

The robot takes an **instantaneous snapshot** of the network and its robots, **with multiplicity detection** (“zero”, “one”, or “more than one” robots).

Compute

Based on this observation, it **decides to stay idle or to move to some neighbouring node**.

Move

In the latter case it **instantaneously moves** towards its destination.

Identical oblivious asynchronous robots

Identical

Robots have no IDs. They execute the same program.


Oblivious

The robots have no memory of observations, computations and moves made in previous cycles.


Asynchronous

The time between Look, Compute, and Move operations is finite but unbounded.

Some remarks



Some remarks



Related work

In the plane



Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
 - Flocchini et al., ISAAC'99, asynchronous model
 - Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
 - Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
 - Flocchini et al., TCS'05 - limited visibility
 - Agmon, Peleg, SODA'04, fault tolerant gathering
 - Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings

Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
 - Geliebke et al., ICALP'03, gathering assuming multiplicity detection
 - Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
 - Flocchini et al., TCS'05 - limited visibility
 - Agmon, Peleg, SODA'04, fault tolerant gathering
 - Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings

Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
 - Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
 - Flocchini et al., TCS'05 - limited visibility
 - Agmon, Peleg, SODA'04, fault tolerant gathering
 - Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings

Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
- Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
 - Flocchini et al., TCS'05 - limited visibility
 - Agmon, Peleg, SODA'04, fault tolerant gathering
 - Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings

Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
- Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
- Flocchini et al., TCS'05 - limited visibility
 - Agmon, Peleg, SODA'04, fault tolerant gathering
 - Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings

Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
- Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
- Flocchini et al., TCS'05 - limited visibility
- Agmon, Peleg, SODA'04, fault tolerant gathering

• Czyzowicz et al., CPODS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings



Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
- Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
- Flocchini et al., TCS'05 - limited visibility
- Agmon, Peleg, SODA'04, fault tolerant gathering
- Czyzowicz et al., OPODIS'06, gathering of few fat robots

• Examples

- Klasing et al., ISAAC'06, gathering in rings



Related work

In the plane

- Suzuki, Yamashita, SIAMJC'99, semi-synchronous model
- Flocchini et al., ISAAC'99, asynchronous model
- Cieliebak et al., ICALP'03, gathering assuming multiplicity detection
- Prencipe, SIROCCO'05, gathering unsolvable without multiplicity detection
- Flocchini et al., TCS'05 - limited visibility
- Agmon, Peleg, SODA'04, fault tolerant gathering
- Czyzowicz et al., OPODIS'06, gathering of few fat robots

In graphs

- Klasing et al., ISAAC'06, gathering in rings



Smallest exploring team

Smallest exploring team

The **minimum number of robots** that can explore a n -node ring is denoted by $\rho(n)$.

Definition

We say that exploration of a n -node ring is possible with k robots, if there exists an algorithm enabling the robots to perform exploration with stop starting from any initial configuration of the k robots without multiplicity (at most one robot per node).

Smallest exploring team

Smallest exploring team

The **minimum number of robots** that can explore a n -node ring is denoted by $\rho(n)$.

Definition

We say that **exploration of a n -node ring is possible with k robots**, if there exists an algorithm enabling the robots to perform exploration with stop **starting from any initial configuration** of the k robots **without multiplicity** (at most one robot per node).

Our results

Lemma

Exploration of a n -node ring by k robots is

- impossible if $k|n$ but $k \neq n$;
- possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Main result

$$\rho(n) \in \Theta(\log n)$$

- There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.
- $\rho(n) \in O(\log n)$

Our results

Lemma

Exploration of a n -node ring by k robots is

- impossible if $k|n$ but $k \neq n$;
- possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Main result


$$\rho(n) \in \Theta(\log n)$$

- There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.
- $\rho(n) \in O(\log n)$

Lower bound (1/2)

Lemma


Impossible to stop
(and sometimes to
explore) when $k|n$.



Lower bound (1/2)

Lemma

Impossible to stop
(and sometimes to
explore) when $k|n$.



Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

- Let n be the least common multiple of integers $1, 2, \dots, q$.
- From the previous slide, we have $\rho(n) \geq q + 1$.
- The Prime Number Theorem implies $\frac{\ln n}{q} \rightarrow 1$.
- This implies the existence of a constant c such that, for infinitely many n , $\rho(n) \geq c \log n$.

Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

- Let n be the least common multiple of integers $1, 2, \dots, q$.
 - From the previous slide, we have $\rho(n) \geq q + 1$.
 - The Prime Number Theorem implies $\frac{\ln n}{q} \rightarrow 1$.
 - This implies the existence of a constant c such that, for infinitely many n , $\rho(n) \geq c \log n$.

Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

- Let n be the least common multiple of integers $1, 2, \dots, q$.
- From the previous slide, we have $\rho(n) \geq q + 1$.
- The Prime Number Theorem implies $\frac{\ln n}{n} \rightarrow 1$.
- This implies the existence of a constant c such that, for infinitely many n , $\rho(n) \geq c \log n$.

Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

- Let n be the least common multiple of integers $1, 2, \dots, q$.
- From the previous slide, we have $\rho(n) \geq q + 1$.
- The Prime Number Theorem implies $\frac{\ln n}{q} \rightarrow 1$.
 - This implies the existence of a constant c such that, for infinitely many n , $\rho(n) \geq c \log n$.

Lower bound (2/2)

Theorem

There exists a constant c such that, for infinitely many n , we have $\rho(n) \geq c \log n$.

Proof

- Let n be the least common multiple of integers $1, 2, \dots, q$.
- From the previous slide, we have $\rho(n) \geq q + 1$.
- The Prime Number Theorem implies $\frac{\ln n}{q} \rightarrow 1$.
- This implies the existence of a constant c such that, for infinitely many n , $\rho(n) \geq c \log n$.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

- Take j such that $\frac{p_j\#}{13\#} \leq n < \frac{p_{j+1}\#}{13\#}$. We have $\rho(n) \leq p_{j+1}$.
(all primes in $\{17, \dots, p_{j+1}\}$ divide $n \implies n \geq \frac{p_{j+1}\#}{13\#}$)
- From [Ruiz, Math. Gaz. '97], we have $\frac{\ln(p_j\#)}{p_j} \rightarrow 1$.
- Hence $\rho(n) \leq p_{j+1} \in O(\log n)$.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

- Take j such that $\frac{p_j\#}{13\#} \leq n < \frac{p_{j+1}\#}{13\#}$. We have $\rho(n) \leq p_{j+1}$.
(all primes in $\{17, \dots, p_{j+1}\}$ divide $n \implies n \geq \frac{p_{j+1}\#}{13\#}$)
- From [Ruiz, Math. Gaz. '97], we have $\frac{\ln(p_j\#)}{p_j} \rightarrow 1$.
- Hence $\rho(n) \leq p_{j+1} \in O(\log n)$.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

- Take j such that $\frac{p_j\#}{13\#} \leq n < \frac{p_{j+1}\#}{13\#}$. We have $\rho(n) \leq p_{j+1}$.
(all primes in $\{17, \dots, p_{j+1}\}$ divide $n \implies n \geq \frac{p_{j+1}\#}{13\#}$)

From [Ruiz, Math. Gaz. '97], we have $\frac{\ln(p\#)}{p} \rightarrow 1$.

Hence $\rho(n) \leq p_{j+1} \in O(\log n)$.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

- Take j such that $\frac{p_j\#}{13\#} \leq n < \frac{p_{j+1}\#}{13\#}$. We have $\rho(n) \leq p_{j+1}$.
(all primes in $\{17, \dots, p_{j+1}\}$ divide $n \implies n \geq \frac{p_{j+1}\#}{13\#}$)
- From [Ruiz, Math. Gaz. '97], we have $\frac{\ln(p_j\#)}{p_j} \rightarrow 1$.

• Hence $\rho(n) \leq p_{j+1} \in O(\log n)$.

Upper bound

Lemma

Exploration is possible if $\gcd(n, k) = 1$, for $k \geq 17$.

Theorem

The size $\rho(n)$ of the smallest exploring team is in $O(\log n)$.

Proof

Let p_j be the j -th prime, and $p_j\# = \prod_{i=1}^j p_i$ the p_j -primorial.

- Take j such that $\frac{p_j\#}{13\#} \leq n < \frac{p_{j+1}\#}{13\#}$. We have $\rho(n) \leq p_{j+1}$.
(all primes in $\{17, \dots, p_{j+1}\}$ divide $n \implies n \geq \frac{p_{j+1}\#}{13\#}$)
- From [Ruiz, Math. Gaz. '97], we have $\frac{\ln(p_j\#)}{p_j} \rightarrow 1$.
- Hence $\rho(n) \leq p_{j+1} \in O(\log n)$.

Some definitions


Interdistance

Minimum distance taken over all pairs of distinct robots.

Here interdistance=2.

Block

Maximal set of robots, of size at least 2, forming a line with a robot every d nodes.
(d =interdistance)



Some definitions


Interdistance

Minimum distance taken over all pairs of distinct robots.

Here interdistance=2.

Block

Maximal set of robots, of size at least 2, forming a line with a robot every d nodes.
(d =interdistance)



Some definitions


Interdistance

Minimum distance taken over all pairs of distinct robots.

Here interdistance=2.

Block

Maximal set of robots, of size at least 2, forming a line with a robot every d nodes.
($d=\text{interdistance}$)



Our algorithm

Set-Up Phase

Goal: to transform the (arbitrary) initial configuration into a configuration of interdistance 1 where there is a single block or two blocks of the same size.

Method: decrease the number of blocks whenever possible.
Otherwise, decrease the interdistance.


Tower-Creation Phase

Goal: to create one or two multiplicities inside each block;
furthermore a number of robots become uniquely identified as
explorers.


Exploration Phase

Goal: to perform exploration thanks to the explorers until
reaching an identified final configuration.


An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example




An example



An example



An example



Conclusion and perspectives

Open problem

- Cycles: $\Theta(\log n)$
- Trees of maximum degree 3: $\Theta(\log n / \log \log n)$
- Arbitrary trees: $\Theta(n)$

What about arbitrary graphs (of maximum degree 3)?

Perspectives

- Limited visibility
- Fault tolerant protocols

Conclusion and perspectives

Open problem

- Cycles: $\Theta(\log n)$
- Trees of maximum degree 3: $\Theta(\log n / \log \log n)$
- Arbitrary trees: $\Theta(n)$

What about arbitrary graphs (of maximum degree 3)?

Perspectives

- Limited visibility
- Fault tolerant protocols

Arcachon (Bordeaux, France)



DISC 2008

22nd International Symposium on Distributed Computing
September 22-24, 2008, Arcachon, France.

Submission: May 4, 2008

disc08.labri.fr

Thank You
for your attention