


Deciding the Sequentiality of a Finitely Ambiguous Max-Plus automaton

Ines Klimann, Sylvain Lombardy, Jean Mairesse & Christophe Prieur


LIAFA, CNRS (UMR 7089) - Université Paris 7
Paris - France




- Automata in which every transition requires some time \longrightarrow weight.




- Automata in which every transition requires some time \longrightarrow weight.
- The weight of a path is the **sum** of weights of its transitions.




- Automata in which every transition requires some time \longrightarrow weight.
- The weight of a path is the **sum** of weights of its transitions.
- The time required to read a word u is the **maximal** time among all the successful paths labeled by u .





- Automata in which every transition requires some time \longrightarrow weight.
- The weight of a path is the **sum** of weights of its transitions.
- The time required to read a word u is the **maximal** time among all the successful paths labeled by u .
- \longrightarrow Max-plus rational series: $S = \bigoplus \langle S, u \rangle u$




- Automata in which every transition requires some time \longrightarrow weight.
- The weight of a path is the **sum** of weights of its transitions.
- The time required to read a word u is the **maximal** time among all the successful paths labeled by u .
- \longrightarrow Max-plus rational series: $S = \bigoplus \langle S, u \rangle u$
- The “zero” element is $-\infty$






- The **equivalence** of Max-plus automata over \mathbb{Z} is **undecidable** (Krob, 94)




- The **equivalence** of Max-plus automata over \mathbb{Z} is **undecidable** (Krob, 94)
- The **positivity** of Max-plus automata over \mathbb{Z} is **undecidable** (Krob, 94)




Sub-classes of Max-plus automata and series

- Sequential (deterministic): Seq




Sub-classes of Max-plus automata and series

- **Sequential** (deterministic): **Seq**
- **Unambiguous**: at most one successful path for each word: **NAmb**



Sub-classes of Max-plus automata and series


- Sequential (deterministic): Seq
- Unambiguous: at most one successful path for each word: NAmb
- Finite union of sequentials: FSeq




Sub-classes of Max-plus automata and series

- Sequential (deterministic): Seq
- Unambiguous: at most one successful path for each word: NAmb
- Finite union of sequentials: FSeq
- Finite union of unambiguous: FAmb \Leftrightarrow
Finitely ambiguous: bounded number of successful paths for each word


Def: Series $S \in$ class Cls iff \exists automaton $A \in$ Cls such that A realizes S .




Example: $\text{NAmb} \cap \text{FSeq} \cap \overline{\text{Seq}}$





$$\langle S, a^n \rangle = \begin{cases} n & \text{if } n \text{ even} \\ 0 & \text{otherwise} \end{cases}$$






$$\langle S, u \rangle = \max(|u|_a, |u|_b).$$







$$\langle S, a^{n_1} b^{m_1} a^{n_2} b^{m_2} \dots \rangle = \sum_{n_i \text{ even}} n_i$$





Example: $\mathbf{FAmb} \cap \mathbf{FSeq} \cup \mathbf{NAmb}$




$$\langle S, a^{n_1} b^{m_1} a^{n_2} b^{m_2} \dots \rangle = \max\left(\sum_{n_i \text{ even}} n_i, \sum_{m_j \text{ even}} m_j \right)$$








- If $S \in \text{NAmb}$, it is decidable whether $S \in \text{Seq}$. (Mohri 97, Choffrut 77)





- If $S \in \text{NAmb}$, it is decidable whether $S \in \text{Seq}$. (Mohri 97, Choffrut 77)
- **NEW:** If $S \in \text{FAmb}$, it is decidable whether $S \in \text{NAmb}$ (and therefore, whether $S \in \text{Seq}$).










New method:





New method:



New method:




New method:



Finite union of unambiguous automata:

$$\mathcal{A} = \bigcup_{i=1}^n \mathcal{A}_i$$

Let \mathcal{P} be the product of all \mathcal{A}_i (with coefficients in \mathbb{Z}^n).




Finite union of unambiguous automata:

$$\mathcal{A} = \bigcup_{i=1}^n \mathcal{A}_i$$

Let \mathcal{P} be the product of all \mathcal{A}_i (with coefficients in \mathbb{Z}^n).

• i is a **victorious coordinate** of a circuit θ iff it has a maximal weight on θ .




Finite union of unambiguous automata:

$$\mathcal{A} = \bigcup_{i=1}^n \mathcal{A}_i$$

Let \mathcal{P} be the product of all \mathcal{A}_i (with coefficients in \mathbb{Z}^n).

- i is a **victorious coordinate** of a circuit θ iff it has a maximal weight on θ .
- i is a **victorious** on a path π iff i is victorious on every sub-circuit of π .




Finite union of unambiguous automata:

$$\mathcal{A} = \bigcup_{i=1}^n \mathcal{A}_i$$

Let \mathcal{P} be the product of all \mathcal{A}_i (with coefficients in \mathbb{Z}^n).


- i is a **victorious coordinate** of a circuit θ iff it has a maximal weight on θ .
- i is a **victorious** on a path π iff i is victorious on every sub-circuit of π .
- $\bigcup \mathcal{A}_i$ verifies the **dominance property** iff $\forall \pi$ of \mathcal{P} , $\text{Vict}(\pi) \neq \emptyset$.





Theorem: Let S realized by $\bigcup A_i$.

$S \in \text{NAmb}$ iff **dominance property** holds on $\bigcup A_i$.


Then, an equivalent unambiguous automaton can effectively be computed.





Construction of the unambiguous automaton





$$k = \min(i + x, j + y)$$





Construction of the unambiguous automaton





Construction of the unambiguous automaton





$$k = \min(i+x, j+y)$$



Construction of the unambiguous automaton




$$k = \min(i+x, j+y)$$




Results:

- Classification of rational series




Results:

- Classification of rational series
- New proof of the decomposition of finitely ambiguous automata



Results:

- Classification of rational series
- New proof of the decomposition of finitely ambiguous automata
- Sequentialization on a larger family of series



Results:

- Classification of rational series
- New proof of the decomposition of finitely ambiguous automata
- Sequentialization on a larger family of series

Open questions:

- Sequentialization on any rational max-plus series
- Decidability of **NAmb**
- *etc...*

